


20



C/22

## Ремень приводной тип VB (тип SFS по ISO 4184)

### Стандартные длины для ремней 20 (в мм)

Длина по наруж. поверх.	Расчетн. длина
950	900
1050	1000
1110	1060
1170	1120
1230	1180
1300	1250
1370	1320
1450	1400
1550	1500
1650	1600
1750	1700
1850	1800
1950	1900
2050	2000
2170	2120
2290	2240
2410	2360
2550	2500
2700	2650
2850	2800
3050	3000
3200	3150
3400	3350
3600	3550
3800	3750
4050	4000
4300	4250
4550	4500
5050	5000
5350	5300
5650	5600
6050	6000

### Стандартные длины для ремней C/22 (в дюймах и мм)

Обозн. (длина в дюймах)	Длина по наруж. поверх.	Расчетн. длина	Обозн. (длина в дюймах)	Длина по наруж. поверх.	Расчетн. длина
C 43	1148	1090	C 105	2725	2667
C 47	1258	1200	C 106	2750	2692
C 48	1273	1215	C 108	2808	2750
C 49	1308	1250	C 110	2858	2800
C 51	1353	1295	C 112	2903	2845
C 52	1378	1320	C 114	2954	2896
C 53	1408	1350	C 115	2979	2921
C 54	1433	1375	C 116	3008	2950
C 55	1458	1400	C 117	3023	2965
C 56	1483	1425	C 118	3058	3000
C 57	1508	1450	C 120	3106	3048
C 58	1533	1475	C 122	3157	3099
C 59	1558	1500	C 124	3208	3150
C 60	1582	1524	C 126	3258	3200
C 61	1608	1550	C 128	3308	3250
C 62	1632	1574	C 130	3360	3302
C 63	1658	1600	C 132	3408	3350
C 65	1708	1650	C 134	3462	3404
C 66	1734	1676	C 136	3508	3450
C 67	1758	1700	C 138	3563	3505
C 68	1785	1727	C 140	3608	3550
C 69	1808	1750	C 142	3665	3607
C 70	1836	1778	C 144	3716	3658
C 71	1858	1800	C 146	3758	3700
C 72	1887	1829	C 148	3808	3750
C 73	1912	1854	C 150	3868	3810
C 74	1938	1880	C 158	4058	4000
C 75	1958	1900	C 162	4158	4100
C 76	1988	1930	C 167	4308	4250
C 77	2014	1956	C 173	4452	4394
C 78	2039	1981	C 177	4558	4500
C 79	2058	2000	C 180	4630	4572
C 80	2090	2032	C 187	4808	4750
C 81	2118	2060	C 190	4884	4826
C 82	2141	2083	C 195	5011	4953
C 83	2166	2108	C 197	5058	5000
C 83 1/2	2178	2120	C 208	5358	5300
C 84	2192	2134	C 210	5392	5334
C 85	2217	2159	C 220	5658	5600
C 86	2242	2184	C 225	5773	5715
C 87	2268	2210	C 236	6058	6000
C 88	2298	2240	C 240	6154	6096
C 89	2319	2261	C 248	6358	6300
C 90	2344	2286	C 264	6758	6700
C 92	2395	2337	C 270	6916	6858
C 93	2418	2360	C 280	7158	7100
C 94	2446	2388	C 295	7558	7500
C 95	2471	2413	C 300	7678	7620
C 96	2496	2438	C 315	8058	8000
C 97	2522	2464			
C 98	2558	2500			
C 99	2583	2525			
C 100	2598	2540			
C 101	2618	2560			
C 102	2649	2591			
C 104	2700	2642			