



Ремень приводной тип VB (тип SFS по ISO 4184)

V/17

Стандартные длины для ремней V/17 (в дюймах и мм)

Обозн. (длина в дюймах)	Длина по наруж. поверх.	Расчетн. длина	Обозн. (длина в дюймах)	Длина по наруж. поверх.	Расчетн. длина	Обозн. (длина в дюймах)	Длина по наруж. поверх.	Расчетн. длина
V 23	610	570	V 59	1540	1500	V 108	2790	2750
V 24	655	615	V 60	1565	1525	V 110	2840	2800
V 25	670	630	V 61	1590	1550	V 112	2885	2845
V 26	690	650	V 62	1615	1575	V 114	2940	2900
V 26 1/2	710	670	V 63	1640	1600	V 115	2961	2921
V 27	726	686	V 64	1665	1625	V 116	2990	2950
V 28	750	710	V 65	1690	1650	V 118	3040	3000
V 29	765	725	V 66	1716	1676	V 120	3088	3048
V 30	790	750	V 67	1740	1700	V 122	3139	3099
V 31	815	775	V 68	1765	1725	V 124	3190	3150
V 32	840	800	V 69	1790	1750	V 126	3240	3200
V 32 1/2	865	825	V 70	1815	1775	V 128	3290	3250
V 33	876	836	V 71	1840	1800	V 130	3342	3302
V 34	890	850	V 72	1869	1829	V 132	3390	3350
V 34 1/2	915	875	V 73			V 134	3444	3404
V 35	929	889	V 74	1920	1880	V 136	3490	3450
V 36	940	900	V 75	1940	1900	V 138	3545	3505
V 37	965	925	V 76	1970	1930	V 140	3590	3550
V 37 1/2	990	950	V 77	1990	1950	V 142	3640	3600
V 38	1005	965	V 78	2021	1981	V 144	3698	3658
V 38 1/2	1015	975	V 79	2040	2000	V 146	3740	3700
V 39	1040	1000	V 80	2072	2032	V 148	3790	3750
V 40	1056	1016	V 81	2100	2060	V 150	3850	3810
V 40 1/2	1070	1030	V 82	2123	2083	V 152	3901	3861
V 41	1080	1040	V 83	2140	2100	V 154	3952	3912
V 41 1/2	1090	1050	V 83 1/2	2160	2120	V 155	3990	3950
V 42	1100	1060	V 84	2174	2134	V 156	4002	3962
V 42 1/2	1115	1075	V 85	2200	2160	V 158	4040	4000
V 43	1130	1090	V 86	2240	2200	V 160	4104	4064
V 43 1/4	1140	1100	V 87	2250	2210	V 162	4155	4115
V 44	1160	1120	V 88	2280	2240	V 165	4240	4200
V 45	1190	1150	V 89	2301	2261	V 167	4290	4250
V 45 1/2	1203	1163	V 90	2326	2286	V 173	4434	4394
V 46	1215	1175	V 91	2340	2300	V 175	4490	4450
V 46 1/2	1220	1180	V 92	2377	2337	V 177	4540	4500
V 47	1240	1200	V 93	2400	2360	V 180	4612	4572
V 48	1255	1215	V 94	2428	2388	V 187	4790	4750
V 48 1/2	1265	1225	V 95	2453	2413	V 195	4993	4953
V 49	1290	1250	V 96	2478	2438	V 197	5040	5000
V 50	1315	1275	V 97	2505	2465	V 208	5340	5300
V 51	1340	1300	V 98	2540	2500	V 210	5374	5334
V 52	1360	1320	V 99	2555	2515	V 220	5640	5600
V 52 1/2	1375	1335	V 100	2580	2540	V 236	6040	6000
V 53	1390	1350	V 101	2605	2565	V 240	6136	6096
V 53 1/2	1400	1360	V 102	2640	2600	V 248	6340	6300
V 54	1412	1372	V 103	2656	2616	V 264	6740	6700
V 55	1440	1400	V 104	2690	2650	V 276	7040	7000
V 56	1462	1422	V 105	2707	2667	V 280	7140	7100
V 57	1490	1450	V 106	2740	2700			
V 58	1513	1473	V 107	2758	2718			