



# Jako 1/2", 12,7 mm Malli H

## ... H 100


Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	D esipor	Max akseli	Paino kg
14 H 100 FB	14	1F	56,60	55,23	64	-	31	40	-	41	10	24	0,65
16 H 100 FB	16	1F	64,68	63,31	70	-	31	46	-	41	10	28	0,85
18 H 100 FB	18	1F	72,77	71,40	79	-	31	54	-	41	12	32	1,10
19 H 100 FB	19	1F	76,81	75,44	83	-	31	58	-	41	12	34	1,20
20 H 100 FB	20	1F	80,85	79,48	87	-	31	62	-	41	12	35	1,40
21 H 100 FB	21	1F	84,89	83,52	91	-	31	67	-	41	12	38	1,60
22 H 100 FB	22	1F	88,94	87,57	94	-	31	70	-	41	12	41	1,70
24 H 100 FB	24	1F	97,02	95,65	102	-	31	75	-	41	12	45	2,00
26 H 100 FB	26	7F	105,11	103,74	112	81	32	55	8	40	15	32	1,40
28 H 100 FB	28	7F	113,19	111,92	115	88	32	60	8	40	15	35	1,60
30 H 100 FB	30	7F	121,28	119,91	128	97	32	60	8	40	15	35	1,70
32 H 100 FB	32	6F	129,36	127,99	135	105	32	70	-	40	20	40	2,20
36 H 100 FB	36	6F	145,53	144,16	150	118	32	80	-	40	20	45	3,00
40 H 100 FB	40	5F	161,70	160,33	168	135	32	80	-	40	20	45	2,80
44 H 100 FB	44	5F	177,87	176,50	184	150	32	80	-	40	20	45	3,10
48 H 100 FB	48	5F	194,04	192,67	200	170	32	80	-	40	20	45	3,30
60 H 100 FB	60	4	242,55	241,18	*	216	34	80	-	45	20	45	5,50
72 H 100 FB	72	4	291,06	289,69	*	263	34	80	-	45	20	45	7,10
84 H 100 FB	84	4	339,57	338,20	*	312	34	80	-	45	20	45	8,20
96 H 100 FB	96	4	388,08	386,71	*	360	34	80	-	45	20	45	9,90
120 H 100 FB	120	4	485,10	483,73	*	458	34	90	-	50	20	50	13,10




1F




6F



5F



6F



7F

## ... H 150

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	D esipor	Max akseli	Paino kg
14 H 150 FB	14	1F	56,60	55,23	64	-	44	40	-	54	12	24	0,82
16 H 150 FB	16	1F	64,68	63,31	70	-	44	46	-	54	12	28	1,10
18 H 150 FB	18	1F	72,77	71,40	79	-	44	54	-	54	12	32	1,50
19 H 150 FB	19	1F	76,81	75,44	83	-	44	58	-	54	12	34	1,70
20 H 150 FB	20	1F	80,85	79,48	87	-	44	62	-	54	12	35	1,80
21 H 150 FB	21	1F	84,89	83,52	91	-	44	67	-	54	12	38	2,20
22 H 150 FB	22	1F	88,94	87,57	94	-	44	70	-	54	12	41	2,30
24 H 150 FB	24	1F	97,02	95,65	102	-	44	75	-	54	12	45	2,60
26 H 150 FB	26	7F	105,11	103,74	108	81	45	55	18	53	15	32	1,70
28 H 150 FB	28	7F	113,19	111,92	115	88	45	60	18	53	15	35	1,90
30 H 150 FB	30	7F	121,28	119,91	128	97	45	60	18	53	15	35	2,10
32 H 150 FB	32	6F	129,36	127,99	135	105	45	70	-	53	20	40	2,60
36 H 150 FB	36	6F	145,53	144,16	150	118	45	80	-	53	20	45	3,20
40 H 150 FB	40	8F	161,70	160,33	168	135	45	80	-	-	20	45	3,80
44 H 150 FB	44	8F	177,87	176,50	184	150	45	80	-	-	20	45	3,70
48 H 150 FB	48	8F	194,04	192,67	200	170	45	80	-	-	20	45	4,00
60 H 150 FB	60	9	242,55	241,18	*	216	46	85	-	-	20	48	5,10
72 H 150 FB	72	9	291,06	289,69	*	263	46	85	-	-	20	48	7,90
84 H 150 FB	84	9	339,57	338,20	*	312	46	85	-	-	20	48	8,90
96 H 150 FB	96	9	388,08	386,71	*	360	46	85	-	-	20	48	10,10
120 H 150 FB	120	4	485,10	483,73	*	458	46	95	-	55	24	55	17,20

\* Pyörässä ei ole laippaa.

Materiaali: Z < 36 teräs, Z > 36 valurauta

Til nr esimer 18 H 100 FB

Pintakäsittely: Musta fosfatoi


Esiporattu  
Leveys(1/100 tuum)  
Malli  
Hammasluku

Varastointi Ruotsissa Hammasluvut Z 14 - 48, leveydet 100, 150 och 200


# Jako 1/2", 12,7 mm Malli H

## ...H 200

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	D esipor	Max akseli	Paino kg
14 H 200 FB	14	1F	56,60	55,23	64	-	58	40	-	68	-	24	1,10
16 H 200 FB	16	1F	64,68	63,61	70	-	58	46	-	68	15	28	1,40
18 H 200 FB	18	1F	72,77	71,40	79	-	58	54	-	68	15	32	1,80
19 H 200 FB	19	1F	76,81	75,44	83	-	58	58	-	68	15	34	2,10
20 H 200 FB	20	1F	80,85	79,48	87	-	58	62	-	68	15	35	2,30
21 H 200 FB	21	1F	84,89	83,52	91	-	58	67	-	68	15	38	2,60
22 H 200 FB	22	1F	88,94	87,57	94	-	58	70	-	68	15	41	2,80
24 H 200 FB	24	1F	97,02	95,65	102	-	58	75	-	68	15	45	3,40
26 H 200 FB	26	7F	105,11	103,74	112	81	58	60	24	66	15	35	2,30
28 H 200 FB	28	7F	113,19	111,92	115	88	58	60	24	66	15	35	2,50
30 H 200 FB	30	7F	121,28	119,91	128	97	58	80	24	66	15	40	2,90
32 H 200 FB	32	7F	129,36	127,99	135	105	58	70	19	66	20	40	3,20
36 H 200 FB	36	7F	145,53	144,16	150	118	58	80	19	66	20	45	3,80
40 H 200 FB	40	10	161,70	160,33	168	135	58	80	-	45	20	45	4,10
44 H 200 FB	44	10	177,87	176,50	184	150	58	80	-	45	20	45	4,40
48 H 200 FB	48	10	194,04	192,67	200	170	58	80	-	45	20	48	5,10
60 H 200 FB	60	11	242,55	241,18	*	216	60	90	-	50	20	50	7,10
72 H 200 FB	72	11	291,06	289,69	*	263	60	90	-	50	20	50	8,00
84 H 200 FB	84	11	339,57	338,20	*	312	60	90	-	50	20	50	12,00
96 H 200 FB	96	11	388,08	386,71	*	360	60	90	-	50	20	50	13,60
120 H 200 FB	120	9	485,10	483,73	*	458	60	100	-	-	24	57	16,60




8F




9

## ... H 300

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	D esipor	Max akseli	Paino kg
16 H 300 FB	16	1F	64,68	63,61	70	-	84	46	-	94	-	28	2,00
18 H 300 FB	18	1F	72,77	71,40	79	-	84	54	-	94	-	32	2,60
19 H 300 FB	19	1F	76,81	75,44	83	-	84	58	-	94	-	34	2,90
20 H 300 FB	20	1F	80,85	79,48	87	-	84	62	-	94	-	35	3,20
21 H 300 FB	21	1F	84,89	83,52	91	-	84	67	-	94	-	38	3,60
22 H 300 FB	22	1F	88,94	87,57	94	-	84	70	-	94	-	41	4,00
24 H 300 FB	24	1F	97,02	95,65	102	-	84	75	-	94	-	45	4,70
26 H 300 FB	26	7F	105,11	103,74	112	81	84	60	35	92	15	35	3,30
28 H 300 FB	28	7F	113,19	111,92	115	88	84	60	35	92	15	35	3,60
30 H 300 FB	30	7F	121,28	119,91	128	97	84	70	35	92	15	40	4,20
32 H 300 FB	32	7F	129,36	127,99	135	105	84	70	35	92	20	40	4,30
36 H 300 FB	36	7F	145,53	144,16	150	118	84	80	35	92	20	45	5,20
40 H 300 FB	40	10	161,70	160,33	168	135	84	80	-	55	20	45	5,60
44 H 300 FB	44	10	177,87	176,50	184	150	84	80	-	55	20	45	5,90
48 H 300 FB	48	10	194,04	192,67	200	170	84	85	-	55	20	48	6,60
60 H 300 FB	60	11	242,55	241,18	*	216	86	100	-	55	20	57	9,90
72 H 300 FB	72	11	291,06	289,69	*	263	86	100	-	55	20	57	13,00
84 H 300 FB	84	11	339,57	338,20	*	312	86	100	-	55	20	57	15,10
96 H 300 FB	96	11	388,08	386,71	*	360	86	100	-	55	20	57	18,20
120 H 300 FB	120	11	485,10	483,73	*	458	86	110	-	65	24	62	26,00



10F



11

Materiaali: Z < 36 teräs, Z > 36 valurauta.

Til nr esimerk 18 H 100 FB

Pintakäsittely: Musta fosfatoi.

Esiporaus  
Leveys (1/100 tuum)  
Malli  
Hammasluku

Varastointi Ruotsissa Hammasluvut Z 14 - 48, leveydet 100, 150 och 200.

# Jako 1/2", 12,7 mm Malli H


## ... H 100

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 14 H 100	14	4	56,60	55,23	62	37	31	-	9	22	1108	28	0,3
BL 16 H 100	16	4	64,68	63,31	67	46	31	-	9	22	1108	28	0,4
BL 18 H 100	18	4	72,77	71,40	80	54	31	-	6	25	1210	32	0,6
BL 19 H 100	19	4	76,81	75,44	84	56	32	-	6	25	1210	32	0,6
BL 20 H 100	20	4	80,85	79,48	88	56	32	-	6	25	1210	32	0,7
BL 21 H 100	21	4	84,89	83,52	88	62	32	-	7	25	1210	32	0,8
BL 22 H 100	22	4	88,94	87,57	94	62	32	-	7	25	1210	32	0,9
BL 23 H 100	23	4	92,98	91,61	98	71	32	-	7	25	1610	42	0,9
BL 24 H 100	24	4	97,02	95,65	100	71	32	-	7	25	1610	42	1,0
BL 25 H 100	25	4	101,06	99,69	104	78	32	-	7	25	1610	42	1,0
BL 26 H 100	26	4	105,11	103,74	108	78	32	-	7	25	1610	42	1,2
BL 27 H 100	27	4	109,15	107,78	113	86	32	-	7	25	1610	42	1,3
BL 28 H 100	28	4	113,19	111,92	118	86	32	-	7	25	1610	42	1,5
BL 30 H 100	30	4	121,28	119,91	129	95	32	-	7	25	1610	42	1,7
BL 32 H 100	32	8	129,36	127,99	137	110	32	82	7	25	1610	42	2,0
BL 36 H 100	36	8	145,53	144,16	151	120	32	82	7	25	1610	42	2,7
BL 40 H 100	40	8	161,70	160,33	168	136	32	82	7	25	1610	42	3,6
BL 48 H 100	48	7	194,04	192,67	199	168	32	110	-	31	2012	50	4,2
BL 60 H 100	60	12	242,55	241,18	*	217	34	110	1	32	2012	50	4,8
BL 72 H 100	72	15	291,06	289,69	*	264	34	110	1	32	2012	50	5,7
BL 84 H 100	84	15	339,57	338,20	*	312	34	110	1	32	2012	50	6,8
BL 96 H 100	96	13	388,08	386,71	*	357	34	120	5,5	45	2517	60	8,2
BL 120 H 10	120	13	485,10	483,73	*	457	34	120	5,5	45	2517	60	12,1


\* Pyörässä ei ole laippaa

Materiaali Z < 48 teräs


Materiaali Z > 60 valurautaa



4



7



8


## ... H 150

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 14 H 150	14	4	56,60	55,23	62	37	45	-	23	22	1108	28	0,5
BL 16 H 150	16	4	64,68	63,31	67	46	45	-	23	22	1108	28	0,5
BL 18 H 150	18	4	72,77	71,40	80	54	45	-	20	25	1210	32	0,6
BL 19 H 150	19	4	76,81	75,44	84	56	45	-	20	25	1210	32	0,7
BL 20 H 150	20	4	80,85	79,48	88	56	45	-	20	25	1210	32	0,8
BL 21 H 150	21	4	84,89	83,52	88	62	45	-	20	25	1210	32	1,0
BL 22 H 150	22	4	88,94	87,57	94	62	45	-	20	25	1210	32	1,2
BL 23 H 150	23	4	92,98	91,61	98	71	45	-	20	25	1610	42	1,3
BL 24 H 150	24	4	97,02	95,65	100	71	45	-	20	25	1610	42	1,0
BL 25 H 150	25	4	101,06	99,69	104	78	45	-	20	25	1610	42	1,2
BL 26 H 150	26	4	105,11	103,74	108	78	45	-	20	25	1610	42	1,4
BL 27 H 150	27	4	109,15	107,78	113	86	45	-	20	25	1610	42	1,6
BL 28 H 150	28	4	113,19	111,92	118	86	45	-	20	25	1610	42	1,8
BL 30 H 150	30	4	121,28	119,91	129	95	45	-	20	25	1610	42	2,0
BL 32 H 150	32	8	129,36	127,99	137	110	45	82	20	25	1610	42	2,3
BL 36 H 150	36	8	145,53	144,16	151	120	45	82	20	25	1610	42	3,1
BL 40 H 150	40	8	161,70	160,33	168	138	45	82	30	25	1610	42	4,0
BL 48 H 150	48	8	194,04	192,67	199	168	45	110	13	31	2012	50	4,8
BL 60 H 150	60	15	242,55	241,18	*	217	46	110	7	32	2012	50	5,4
BL 72 H 150	72	15	291,06	289,69	*	264	46	110	7	32	2012	50	6,5
BL 84 H 150	84	15	339,57	338,20	*	312	46	110	7	32	2012	50	8,4
BL 96 H 150	96	15	388,08	386,71	*	357	46	120	0,5	45	2517	60	11,0
BL 120 H 15	120	15	485,10	483,73	*	457	46	120	0,5	45	2517	60	14,8


\* Pyörässä ei ole laippaa.

Materiaali Z < 48 teräs

Materiaali Z > 60 valurautaa



12



13


... H 200

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 16 H 200	16	4	64,68	63,61	67	46	58	-	36	22	1108	28	0,7
BL 18 H 200	18	4	72,77	71,40	80	56	58	-	33	25	1210	32	0,8
BL 19 H 200	19	4	76,81	75,44	84	56	58	-	33	25	1210	32	0,9
BL 20 H 200	20	4	80,85	79,48	88	56	58	-	33	25	1210	32	1,0
BL 21 H 200	21	4	84,89	83,52	88	62	58	-	33	25	1610	42	1,7
BL 22 H 200	22	4	88,94	87,57	94	62	58	-	33	25	1610	42	1,5
BL 23 H 200	23	4	92,98	91,61	98	71	58	-	33	25	1610	42	1,8
BL 24 H 200	24	4	97,02	95,65	100	71	58	-	33	25	1610	42	1,5
BL 25 H 200	25	4	101,06	99,69	104	78	58	-	33	25	1610	42	1,5
BL 26 H 200	26	4	105,11	103,74	108	78	58	-	33	25	1610	42	1,8
BL 27 H 200	27	4	109,15	107,78	113	86	58	-	33	25	1610	42	1,9
BL 28 H 200	28	4	113,19	111,92	118	86	58	-	33	25	1610	42	1,9
BL 30 H 200	30	4	121,28	119,91	129	95	58	-	33	25	1610	42	2,3
BL 32 H 200	32	4	129,36	127,99	137	110	58	-	26	32	2012	50	3,0
BL 36 H 200	36	8	145,53	144,16	151	120	58	102	36	32	2012	50	3,0
BL 40 H 200	40	8	161,70	160,33	168	136	58	110	36	32	2012	50	3,6
BL 48 H 200	48	8	194,04	192,67	199	168	58	120	13	45	2517	60	4,6
BL 60 H 200	60	15	242,55	214,18	*	217	60	120	7,5	45	2517	60	7,0
BL 72 H 200	72	15	291,06	289,69	*	264	60	120	7,5	45	2517	60	8,0
BL 84 H 200	84	15	339,57	338,20	*	312	60	120	7,5	45	2517	60	9,0
BL 96 H 200	96	15	388,08	386,71	*	357	60	120	7,5	45	2517	60	10,0
BL 120 H 200	120	15	485,10	483,73	*	457	60	146	7,5	45	2517	60	13,4


\* Pyörässä ei ole laippaa.

Materiaali Z < 48 teräs


Materiaali Z > 60 valurauta



3



5



15

... H 300

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 19 H 300	19	3	76,81	75,44	84	56	84	-	23	38	1215	32	1,5
BL 20 H 300	20	3	80,85	79,48	88	65	84	-	23	38	1615	42	1,5
BL 21 H 300	21	3	84,89	83,52	94	65	84	-	23	38	1615	42	1,5
BL 22 H 300	22	3	88,94	87,57	94	67	84	-	23	38	1615	42	1,6
BL 23 H 300	23	3	82,98	91,61	98	71	84	-	23	38	1615	42	1,8
BL 24 H 300	24	3	97,02	95,65	104	71	84	-	23	38	1615	42	2,1
BL 25 H 300	25	3	101,06	99,69	104	78	84	-	23	38	1615	42	2,1
BL 26 H 300	26	3	105,11	103,74	108	78	84	-	23	38	1615	42	2,7
BL 27 H 300	27	3	109,15	107,78	113	86	84	-	26	32	2012	50	3,0
BL 28 H 300	28	3	113,19	111,92	118	86	84	-	26	32	2012	50	2,4
BL 30 H 300	30	3	121,28	119,91	129	95	84	-	26	32	2012	50	2,9
BL 32 H 300	32	3	129,36	127,99	137	110	84	-	19,5	45	2517	60	3,3
BL 36 H 300	36	3	145,53	144,16	151	120	84	-	19,5	45	2517	60	4,5
BL 40 H 300	40	5	161,70	160,33	168	136	84	120	19,5	45	2517	60	6,0
BL 48 H 300	48	5	194,04	192,67	199	168	86	120	20,5	45	2517	60	7,6
BL 60 H 300	60	15	242,55	241,18	*	217	86	120	20,5	45	2517	60	8,4
BL 72 H 300	72	15	291,05	289,69	*	264	86	120	20,5	45	2517	60	10,4
BL 84 H 300	84	15	339,57	338,20	*	312	86	120	20,5	45	2517	60	12,5
BL 96 H 300	96	15	388,08	386,71	*	357	86	146	5	76	3030	75	14,4
BL 120 H 300	120	15	485,10	483,73	*	457	86	146	5	76	3030	75	18,8

\* Pyörässä ei ole laippaa.

Materiaali Z < 48 teräs

Materiaali Z > 60 valurauta

Hinnat ilman holkkia

Til.nr esim 18 H 100

Leveys (1/100")

-Malli

Varastointi Ruotsissa

Hammasluku