



**jako 3/8", 9,525 mm Malli L**

**...L 050**


Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Y mm	D esipor.	Max akseli	Pain kg
10 L 050 FB	10	1F	30,32	29,56	37	-	19	22	26	6	13	0,11
12 L 050 FB	12	1F	36,38	35,62	43	-	19	28	26	6	17	0,19
13 L 050 FB	13	1F	39,41	38,65	44	-	19	30	26	6	19	0,21
14 L 050 FB	14	1F	42,45	41,68	48	-	19	33	26	8	20	0,25
15 L 050 FB	15	1F	45,48	44,72	51	-	19	36	26	8	23	0,30
16 L 050 FB	16	1F	48,51	47,75	54	-	19	38	26	8	23	0,33
17 L 050 FB	17	1F	51,54	50,78	57	-	19	40	26	10	24	0,36
18 L 050 FB	18	1F	54,57	53,81	60	-	19	40	26	10	24	0,41
19 L 050 FB	19	1F	57,61	56,84	64	-	19	40	26	10	24	0,45
20 L 050 FB	20	1F	60,64	59,88	67	-	19	46	26	10	28	0,50
21 L 050 FB	21	1F	63,67	62,91	70	-	19	46	26	10	28	0,55
22 L 050 FB	22	1F	66,70	65,94	75	-	19	50	26	10	30	0,62
24 L 050 FB	24	1F	72,77	72,00	79	-	19	50	26	12	30	0,68
26 L 050 FB	26	1F	78,83	78,07	86	-	19	50	26	12	30	0,82
28 L 050 FB	28	1F	84,89	84,13	91	-	19	50	26	12	30	0,92
30 L 050 FB	30	1F	90,96	90,20	97	-	19	50	26	12	30	1,10
32 L 050 FB	32	1F	97,02	96,26	102	-	19	50	26	12	30	1,20
36 L 050 FB	36	6F	109,15	108,39	115	94	19	50	26	12	30	1,00
40 L 050 FB	40	6F	121,28	120,51	128	98	19	50	26	12	30	1,10
44 L 050 FB	44	5F	133,40	132,64	142	108	19	50	26	12	30	1,20
48 L 050 FB	48	5F	145,53	144,77	150	118	19	50	26	12	30	1,30
60 L 050 FB	60	4	191,91	181,15	*	163	19	50	28	15	30	1,30
72 L 050 FB	72	4	218,30	217,53	*	199	19	50	28	15	30	1,70
84 L 050 FB	84	4	254,68	253,92	*	236	19	50	28	15	30	1,90




1F



4



5F



6F

**...L 075**

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Y mm	D esipor.	Max akseli	Pain kg
10 L 075 FB	10	1F	30,32	29,56	37	-	25	22	32	8	13	0,20
12 L 075 FB	12	1F	36,38	35,62	43	-	25	28	32	8	17	0,23
13 L 075 FB	13	1F	39,41	38,65	44	-	25	30	32	8	19	0,26
14 L 075 FB	14	1F	42,45	41,68	48	-	25	33	32	8	20	0,32
15 L 075 FB	15	1F	45,48	44,72	51	-	25	36	32	8	23	0,35
16 L 075 FB	16	1F	48,51	47,75	54	-	25	38	32	8	23	0,42
17 L 075 FB	17	1F	51,54	50,78	57	-	25	40	32	10	24	0,45
18 L 075 FB	18	1F	54,57	53,81	60	-	25	40	32	10	24	0,51
19 L 075 FB	19	1F	57,61	56,84	64	-	25	40	32	10	24	0,57
20 L 075 FB	20	1F	60,64	59,88	67	-	25	46	32	10	28	0,63
21 L 075 FB	21	1F	63,67	62,91	70	-	25	46	32	10	28	0,70
22 L 075 FB	22	1F	66,70	65,94	75	-	25	50	32	10	30	0,75
24 L 075 FB	24	1F	72,77	72,00	79	-	25	50	32	12	30	0,85
26 L 075 FB	26	1F	78,83	78,07	86	-	25	50	32	12	30	1,00
28 L 075 FB	28	1F	84,89	84,13	91	-	25	50	32	12	30	1,20
30 L 075 FB	30	1F	90,96	90,20	97	-	25	50	32	12	30	1,40
32 L 075 FB	32	1F	97,02	96,26	102	-	25	50	32	12	30	1,50
36 L 075 FB	36	6F	109,15	108,39	115	94	25	55	32	12	32	1,30
40 L 075 FB	40	6F	121,28	120,51	128	98	25	60	32	12	35	1,60
44 L 075 FB	44	5F	133,40	132,64	142	108	25	60	32	12	35	1,70
48 L 075 FB	48	5F	145,53	144,77	150	118	25	60	32	12	35	1,90
60 L 075 FB	60	4	191,91	181,15	*	163	26	60	35	15	35	1,80
72 L 075 FB	70	4	218,30	217,53	*	199	26	60	35	15	35	2,30
84 L 075 FB	84	4	254,68	253,92	*	236	26	60	35	15	35	2,50

\*Pyörässä ei ole laippaa

Til.nr. esim. 20 L 050 FB



Materiaali: Z < 40 Teräs, > 44 Valurautaa.


Pintakäsittely: Musta fosfatiointi

Varastointi Ruotsissa: Hammasluvut Z 10-60, leveydet 050, 075 ja 100.


# jako 3/8", 9,525 mm Malli L

## ...L 100


Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Y mm	D mm	Max akseli	Pain kg
10 L 100 FB	10	1F	30,32	29,56	37	-	31	22	38	-	13	0,27
12 L 100 FB	12	1F	36,38	35,62	43	-	31	28	38	-	17	0,29
13 L 100 FB	13	1F	39,41	38,65	44	-	31	30	38	-	19	0,30
14 L 100 FB	14	1F	42,45	41,68	48	-	31	33	38	-	20	0,38
15 L 100 FB	15	1F	45,48	44,72	51	-	31	36	38	-	23	0,40
16 L 100 FB	16	1F	48,51	47,75	54	-	31	38	38	-	23	0,51
17 L 100 FB	17	1F	51,54	50,78	57	-	31	40	38	10	24	0,54
18 L 100 FB	18	1F	54,57	53,81	60	-	31	40	38	10	24	0,62
19 L 100 FB	19	1F	57,61	56,84	64	-	31	40	38	10	24	0,69
20 L 100 FB	20	1F	60,64	59,88	67	-	31	46	38	10	28	0,76
21 L 100 FB	21	1F	63,67	62,91	70	-	31	46	38	10	28	0,82
22 L 100 FB	22	1F	66,70	65,94	75	-	31	50	38	10	30	0,92
24 L 100 FB	24	1F	72,77	72,00	79	-	31	50	38	12	30	1,10
26 L 100 FB	26	1F	78,83	78,07	86	-	31	50	38	12	30	1,30
28 L 100 FB	28	1F	84,89	84,13	91	-	31	50	38	12	30	1,40
30 L 100 FB	30	1F	90,96	90,20	97	-	31	50	38	12	30	1,70
32 L 100 FB	32	1F	97,02	96,26	102	-	31	50	38	12	30	1,80
36 L 100 FB	36	7F	109,15	108,39	115	94	32	55	38	12	32	1,50
40 L 100 FB	40	7F	121,28	120,51	128	98	32	60	38	12	35	1,80
44 L 100 FB	44	8F	133,40	132,64	142	108	32	60	-	12	35	1,90
48 L 100 FB	48	8F	145,53	144,77	150	118	32	60	-	12	35	2,10
60 L 100 FB	60	4	191,91	181,15	*	163	32	60	35	15	35	2,00
72 L 100 FB	72	4	218,30	217,53	*	199	32	60	35	15	35	2,50
84 L 100 FB	84	4	254,68	253,92	*	236	32	60	35	15	35	2,70



1F



4



7F


\*Pyörässä ei ole laippaa

Til.nr. esim. 20 L 100 FB

Materiaali: Z < 40 Teräs, > 44 Valurautaa.

Pintakäsit: Musta fosfatointi

Varastointi Ruotsissa Hammasluvut Z 10-60, leveydet 050, 075 ja 100.



8F

# Jako 3/8", 9.525 mm Tyyppi L


## ...L 050

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 18 L 050	18	1	54,57	53,81	62	-	19	47	3	22	1108	28	0,2
BL 19 L 050	19	1	57,61	56,84	62	-	19	47	3	22	1108	28	0,2
BL 20 L 050	20	1	60,64	59,88	67	-	19	48	3	22	1108	28	0,2
BL 21 L 050	21	1	63,67	62,91	67	-	19	48	3	22	1108	28	0,3
BL 22 L 050	22	1	68,70	65,94	73	-	19	51	3	22	1108	28	0,3
BL 23 L 050	23	1	69,73	68,97	73	-	19	51	3	22	1108	28	0,4
BL 24 L 050	24	1	72,77	72,01	80	-	19	58	3	22	1108	28	0,4
BL 25 L 050	25	1	75,80	75,04	80	-	19	58	3	22	1108	28	0,5
BL 26 L 050	26	1	78,83	78,07	88	-	19	58	3	22	1108	28	0,5
BL 27 L 050	27	1	81,86	81,10	88	-	19	58	3	22	1108	28	0,6
BL 28 L 050	28	1	84,89	84,13	94	-	19	58	3	22	1108	28	0,6
BL 30 L 050	30	1	90,96	90,20	98	-	19	58	3	22	1108	28	0,8
BL 32 L 050	32	1	97,02	96,26	100	-	19	58	3	22	1108	28	0,9
BL 36 L 050	36	6	109,15	108,39	113	84	19	58	3	22	1108	28	1,2
BL 40 L 050	40	1	121,28	120,52	129	-	19	90	6	25	1610	42	1,5
BL 48 L 050	48	6	145,53	144,77	151	126	19	90	6	25	1610	42	2,3
BL 60 L 050	60	13	181,91	181,55	*	162	19	90	6	25	1610	42	2,0
BL 72 L 050	72	13	218,30	217,54	*	199	19	90	6	25	1610	42	3,0
BL 84 L 050	84	13	254,68	253,92	*	235	19	90	6	25	1610	42	4,0
BL 96 L 050	96	13	291,06	290,30	*	270	19	90	6	32	2012	50	5,5
BL 120 L 050	120	13	363,83	363,07	*	344	19	90	6	32	2012	50	6,8


\*Pyörässä ei ole laippaa.

Materiaali: Z<60 Teräs


Materiaali: Z>72Valurauta



1



2



4


## ...L 075

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 18 L 075	18	4	54,57	53,81	62	38	25	-	3	22	1108	28	0,2
BL 19 L 075	19	4	57,61	56,84	62	38	25	-	3	22	1108	28	0,3
BL 20 L 075	20	4	60,64	59,88	67	46	25	-	3	22	1108	28	0,3
BL 21 L 075	21	4	63,67	62,91	67	46	25	-	3	22	1108	28	0,4
BL 22 L 075	22	4	68,70	65,94	73	46	25	-	3	22	1108	28	0,4
BL 23 L 075	23	4	69,73	68,97	73	46	25	-	3	22	1108	28	0,4
BL 24 L 075	24	4	72,77	72,01	80	53	25	-	3	22	1108	28	0,5
BL 25 L 075	25	4	75,80	75,04	80	53	25	-	3	22	1108	28	0,5
BL 26 L 075	26	4	78,83	78,07	88	60	25	-	3	22	1108	28	0,6
BL 27 L 075	27	4	81,86	81,10	88	60	25	-	3	22	1108	28	0,7
BL 28 L 075	28	4	84,89	84,13	94	65	25	-	3	22	1108	28	0,7
BL 30 L 075	30	4	90,96	90,20	98	68	25	-	3	22	1108	28	0,9
BL 32 L 075	32	4	97,02	96,26	100	76	25	-	3	22	1108	28	1,0
BL 36 L 075	36	2	109,15	108,39	113	-	25	-	-	25	1610	42	1,2
BL 40 L 075	40	2	121,28	120,52	129	-	25	-	-	25	1610	42	1,7
BL 48 L 075	48	7	145,53	144,77	151	126	25	90	-	25	1610	42	2,5
BL 60 L 075	60	10	181,91	181,15	*	162	25	90	-	25	1610	42	3,0
BL 72 L 075	72	14	218,30	217,54	*	199	25	90	-	25	1610	42	4,0
BL 84 L 075	84	13	254,68	253,92	*	235	25	110	6,6	32	2012	50	5,2
BL 96 L 075	96	13	291,06	290,30	*	270	25	110	6,6	32	2012	50	6,5
BL 120 L 075	120	13	363,83	363,07	*	344	25	110	6,6	32	2012	50	7,6


\*Pyörässä ei ole laippaa.

Materiaali: Z<60 Teräs


Materiaali: Z>72Valurauta



6



7



8

Varastoidaan Ruotsissa.

... L 100

Обозначение	Кол-во зубьев	Тип	Do mm	Dy mm	Df mm	Di mm	W mm	H mm	Z mm	Y mm	Holkki	Max akseli	Paino kg
BL 18 L 100	18	4	54,57	53,81	62	38	32	-	10	22	1108	28	0,2
BL 19 L 100	19	4	57,61	56,84	62	38	32	-	10	22	1108	28	0,3
BL 20 L 100	20	4	60,64	59,88	67	46	32	-	10	22	1108	28	0,4
BL 21 L 100	21	4	63,67	62,91	67	46	32	-	10	22	1108	28	0,4
BL 22 L 100	22	4	68,70	65,94	73	46	32	-	10	22	1108	28	0,4
BL 23 L 100	23	4	69,73	68,97	73	46	32	-	10	22	1108	28	0,5
BL 24 L 100	24	4	72,77	72,01	80	53	32	-	10	22	1108	28	0,6
BL 25 L 100	25	4	75,80	75,04	80	53	32	-	10	22	1108	28	0,6
BL 26 L 100	26	4	78,83	78,07	88	60	32	-	10	22	1108	28	0,7
BL 27 L 100	27	4	81,86	81,10	88	60	32	-	10	22	1108	28	0,8
BL 28 L 100	28	4	84,89	84,13	94	65	32	-	10	22	1108	28	0,8
BL 30 L 100	30	4	90,96	90,20	98	68	32	-	7	25	1210	32	0,9
BL 32 L 100	32	4	97,02	96,26	100	76	32	-	7	25	1210	32	1,0
BL 36 L 100	36	4	109,15	108,39	113	85	32	-	7	25	1610	42	1,4
BL 40 L 100	40	4	121,28	120,52	129	100	32	-	7	25	1610	42	1,7
BL 48 L 100	48	8	145,53	144,77	151	126	32	90	7	25	1610	42	2,7
BL 60 L 100	60	12	181,91	181,15	*	162	32	90	3,5	25	1610	42	3,4
BL 72 L 100	72	14	218,30	217,54	*	199	32	110	-	32	2012	50	4,4
BL 84 L 100	84	14	254,68	253,92	*	235	32	110	-	32	2012	50	6,0
BL 96 L 100	96	14	291,06	290,30	*	270	32	110	-	32	2012	50	7,1
BL 120 L 100	120	14	363,83	363,07	*	344	32	110	-	32	2012	50	8,5

\* Pyörässä ei ole laippaa.

Materiaali Z < 60 teräs

Materiaali Z > 72 valurauta

Esim. tilausnr: 14 L 100

Leveys (1/100")


Malli

Hammasluku


Hinnat ilman holkkia

Holkkihinnat sivulla 30


Varastoidaan Ruotsissa




10




12



13



14



15